

**NORTH GEELONG C BOX TO NORTH SHORE YARD (VIA CORIO INDEPENDENT GOODS LINE - CIGL)**

**DUAL GAUGE**

**1. CLASS OF LOCOMOTIVE AND PERMITTED SPEEDS (KM/H)**

		CLASS OF LOCOMOTIVE		
		G, XR, BL, 81 VL, CLP, CLF, 22 Class	A, B, GM, N, S, X, EL	H, P, T, Y
NORTH GEELONG C BOX to GRAIN LOOP JUNCTION	Freight	20	20	20
GRAIN LOOP JUNCTION to EAST YARD JUNCTION		15	15	15
EAST YARD JUNCTION TO NORTH SHORE YARD		25	25	25
Over Points CGL 37 At 68.54km until whole of train has cleared points		15	15	15
NORTH SHORE and APEX QUARRY & PHOSPHATE SIDINGS	Freight	15	15	15
NORTH SHORE and STANDARD GAUGE SIDINGS	Freight	15	15	15

**2. SPECIAL SPEED RESTRICTIONS**

No Special Speed Restrictions apply.

**3. RULING GRADE LOADS (TONNES)**

	CLASSES OF LOCOMOTIVES												
	G, XR, BL, 81	N	GM, S, X	Mod. A Class	A solo or multi with A	A multi with other class	B	H solo or multi with H, P, T or Y	H multi with other class	T or P solo or multi with H, P, T or Y	T or P multi with other class	Y solo or multi with T, Y, H or P	Y multi with other class
<b>DOWN</b>													
<b>Phosphate Siding to North Shore</b>								1420	1420	1420	1420	1020	1020
<b>North Shore Yard to North Geelong 'C' Box</b>	2280	1520	1520	1420	1420	1420	1420	1015	1015	1015	1015	400	400
<b>UP</b>													
<b>Grain Loop Jctn to North Shore</b>	3170	2135	2135	1830	1830	1830	1830	1420	1420	1420	1420	1270	1270
<b>North Shore Yard to Phosphate Siding</b>								1020	1020	1020	1020	710	710

Authorised Loads for trains to / from the APEX QUARRY SIDING are those applicable between NEWPORT and NORTH GEELONG YARD.

**4. SAFEWORKING SYSTEMS**

Siding Conditions Working is in force between North Shore and Phosphate Siding and within the Apex Quarry Siding and Midway Siding.

Automatic Block Signalling is in force between North Shore Yard and North Geelong 'C' Box.

**5. SPECIAL NOTES**

No Special Notes

**NETWORK SERVICE PLAN**

**NORTH GEELONG C BOX TO NORTH SHORE YARD (VIA CORIO INDEPENDENT GOODS LINE - CIGL)**

**DUAL GAUGE**

**6. DISTANCES FROM MELBOURNE AND CLEAR LENGTH OF CROSSING ROADS**

LOCATION	MARKED DISTANCE FROM MELBOURNE (KM)	CLEAR LENGTH OF CROSSING ROADS (LENGTH IN METRES)	
		NO. 1	NO. 2
NORTH SHORE PHOSPHATE SIDING	67.172	749	632
NORTH SHORE APEX QUARRY SIDING	67.172		
NORTH SHORE A SIDING (SG)	66.210	650	
NORTH SHORE B SIDING (SG)	65.920	900	
NORTH SHORE C SIDING (SG)	66.240	650	
NORTH SHORE D SIDING	66.320	490	
NORTH SHORE E SIDING	66.320	780	
NORTH SHORE K SIDING	66.860	220	
NORTH SHORE L SIDING	66.890	220	

**7. TRACK CLASS**

Track is maintained to class standards for sidings.

**8. PROTECTED LEVEL CROSSINGS**

NAME AND KMS OF NEAREST STATION	LEVEL CROSSING	DISTANCE (KM)	TYPE	LOCATION NUMBER
NORTH SHORE – 67.172	Seabeach Parade	68.234	FL	G0683
	Station Street	67.217	BB	G0672

**BB** – Boom Barriers

**NSW** – R.I.C. Distance from Sydney

**T** – Equipped with Telephone Communication

**CC** – Crib Crossing

**PB** – Pedestrian Barriers

**VIC** – Victorian Broad Gauge

**FL** – Flashing Lights

**PG** – Pedestrian Gates

**IG** – Interlocked Gates

**SG** – Standard Gauge